

[illegible]

WIRE SIZE >0.75mm²-1.5mm²

CAVITY NOTES:

1. CAVITY DESIGN SHOWN IS BASED ON MATERIAL USAGE PBT-GF15.
A USER IS RESPONSIBLE FOR NECESSARY MODIFICATIONS REQUIRED FOR
A SPECIFIC APPLICATION OR MATERIAL.
2. UNLESS OTHERWISE SPECIFIED ALL RADII TO BE 0.30 MM.
3. GENERAL TOLERANCES: +0.20 MAX 10; +0.25 MAX 20.
4. UNDIMENSIONED FEATURES ARE AT THE DISCRETION OF THE COMPONENT DESIGNER.
5. CAVITY TO BE USED WITH SUMITOMO 1.2mm UNSEALED MALE TERMINAL.
6. UNLESS OTHERWISE SPECIFIED, ALL DRAFT TO BE WITHIN DIMENSIONAL TOLERANCE.
7. EXTERNAL CAVITY PROFILE FOR REFERENCE ONLY.

UNSEALED MALE TERMINAL CRIMPING TOOL DIMENSIONS
(FOR REFERENCE ONLY)

5000 PART NUMBER	5000 IEP PART NUMBER	CONDUCTOR PUNCH	INSULATION PUNCH	CONDUCTOR ANVIL	INSULATION ANVIL
MUST-14421-LA	B230-5754				
MUST-14421-4A	B230-5753				
MUST-14421-1A	B230-5752				